



Model PA310 | Wired PresentationPro™



Includes magnetic volume/mute remote

Optional TP-50 tri-pod not included

Portable or installed, solo or used with other speakers, the PA310 is the ideal wired voice and audio amplification solution for any presenter. Projecting rich and big sound, the PA310 is one of the most specified speakers by schools and districts because of its power and durability. It has multiple inputs for voice and audio amplification from computers, mobile devices, microphones and other sources.

PA310 Features

- Rugged steel-reinforced handle for easy mobility
- Volume up / Mute / Volume down controls
- Volume indicator
- Power switch, LED indicator & DC power input jack
- Separate bass, treble controls for quality sound
- 1/4" Line in and line out connect with LCD projectors, computers, whiteboards
- Dual RCA & 3.5mm Aux in jacks for external audio sources
- Mic input for XLR or 1/4" mics
- PI-RC Remote controls volume up / down, mute, speaker power
- Ideal for mobile presenters, classroom and athletic uses
- Includes volume/mute remote control

Specifications

<i>Rated Power Output:</i>	30 watts RMS
<i>Sensitivity for Rated Output:</i>	Line:125 mVrms
<i>Microphone:</i>	4 mVrms
<i>Auxiliary:</i>	250 mVrms
<i>Frequency Response:</i>	60 Hz - 20 kHz ± 3dB
<i>Dispersion Angle:</i>	90° H x 120° V
<i>Speaker:</i>	6.5" full-range speaker
<i>Distortion</i>	1% (at 10W)
<i>Crossover:</i>	L/C - 6dB/Octave @ 4 kHz
<i>Inputs:</i>	Line inputs (2):Hi-Z,RCA(summing L+R)
<i>Balanced mic:</i>	Hi or lo-Z, with phantom power (+15 volts D.C.)
	Unbalanced mic:Lo -Z, 1/4"-phone
<i>Auxiliary:</i>	Hi-Z Mono 1/4"-phone
<i>Line Output:</i>	250mv constant
<i>Remote Control</i>	20' range with 45 degree operating field in front of the speaker
<i>AC Power Requirements:</i>	110 - 125 VAC, 50/60 Hz or 208 - 240 VAC, 50/60 Hz
<i>Dimensions (HWD):</i>	6.25" x 10" x 8.5"
<i>Weight:</i>	10 pounds, shipping weight 13 lbs.
<i>Warranty</i>	6 year from date of purchase for use in school, business, church and government facilities