



THE SIGHTS & SOUNDS  
OF EDUCATION

# Wireless Audio System Transmitter

## WS-T

**This lightweight transmitter has a range\* of up to 300' and is designed for use with the Assistive Listening WS-series or Califone 900 MHz PA products.**

- |                              |                         |
|------------------------------|-------------------------|
| 1. Line Input                | 9. Channel Up           |
| 2. Microphone Input          | 10. Charging Jack       |
| 3. Volume Up                 | 11. Belt Clip           |
| 4. Volume Down               | 12. Walkie-talkie/Mute  |
| 5. Walkie-talkie/Mute Button | 13. TX Power Switch     |
| 6. LCD Screen                | 14. Channel Lock Switch |
| 7. Channel Down              | 15. Power Indicator LED |
| 8. Power On / Off            | 16. Lanyard Hole        |



- Warranty for school use - unlike items purchased from consumer electronics stores whose warranties would be voided if used in schools

Shown with [WS-CR](#) recharging cradle (sold separately)



### <None>"Project Intercept"


Please contact us immediately if you experience any difficulties with your transmitter. Our "Project Intercept" customer service program will quickly repair or replace items under warranty. Simply contact us via phone or email [warranty@califone.com](mailto:warranty@califone.com).

Visit our website at to [register your product](#) and to learn more about the complete line of *Califone*® audio enhancing and visual technology products including: Wired and Wireless public address systems and lecterns, wireless microphones, headphones & headsets, group listening centers, multimedia players, computer peripheral products and installed classroom infrared systems.

*We are proud of helping teachers enhance student understanding and achievements since 1947, with your satisfaction as our first priority.*

This transmitter has a 1 year warranty and service support available through authorized dealers nationwide.

Distributed by:



## Specifications

Operational Range	Low TX Power / Low RX Sens.: > 100' * Low TX Power / High RX Sens.: > 200' * High TX Power / Low RX Sens.: > 200' * High TX Power / High RX Sens.: > 300' * * Line-of-sight required. Range may be lower due to obstructions / interference.
Frequency Response (Mic/Line Inputs)	100 Hz - 8 kHz +/- 3dB
THD + N% (Mic/Line Inputs)	< 3 %
Transmitter Channels	16
Frequency Range	902 - 928 MHz
Power Requirements	Uses 3.7 V / 1800 mAh Li-Ion battery
Transmit Channels	1 (Mono)
Output Power	Low: 5 mW / High: 10 mW
Sensitivity (Mic Input)	50 mV
Sensitivity (Line Input)	250 mV
Usage Time	> 11 hours
Battery Recharge Time	< 13 hours
S/N Ratio	> 60 dB
Product Dimensions	4" x 3" x 1.25"
Product Weight (incl. accessories)	5 oz., shipping weight 1 lb.
Warranty	For use in school, business, church and government facilities for 1 year

### CPSIA

Click here to view the [safety compliances](#) for this product under the Consumer Product Safety Improvement Act

Califone® International Inc. 800-722-0500  
[califone.com](http://califone.com)